

Spectrex SharpEye™ 40/40C-L4B

Integrated UV/IR Flame Detector



The SharpEye 40/40C-L4B UV/IR flame detector is part of the leading, next generation SharpEye 40/40 series.

Featuring fast detection in under five seconds with proven immunity to false alarms, the integrated UV and IR optical sensors detect hydrocarbon-based fuel and gas fires, ensuring flawless performance to keep a SharpEye on your safety!.



Features and benefits

Integrating UV and IR optical sensors for detection of hydrocarbon-based fuel and gas fires.

- Fast detection under five seconds
- Proven false alarm immunity
- Unparalleled reliability - 150,000 hours MTBF
- Wide temperature range:
-40 to +185 °F (-40 to +75 °C)
- Worldwide and regionally certified for hazardous areas
- Performance and reliability approved by recognizable certification bodies
- SIL3 compatible
- Enhanced durability backed up by with five-year warranty
- Smart field of view integrity test, allowing flawless operation
- Innovative UV and IR Built-In-Test - continuously validating the optical integrity and the electronic circuitry
- Multiple output options for maximum compatibility with standard infrastructures
- Plug-and-Play - factory calibrated for immediate use in any fire detection system
- Universal wiring option for fast ordering process
- Three sensitivity levels, adapting to any application
- Two mode heated optics for impeccable performance in challenging environmental conditions

Contents

Features and benefits.....	2
Applications examples.....	3
Specifications.....	4

Applications examples

- Offshore oil and gas installations
- Onshore oil and gas installations and pipelines
- Chemical plants
- Petrochemical plants
- Storage tank farms
- Aircraft hangars
- Power generation facilities
- Automotive industry
- Aerospace industry
- Waste disposal facilities
- Pharmaceutical industry
- Printing industry
- Warehouses
- Paint, polymer, and glue processes
- Light industrial

Specifications

Table 1: General Specifications

Spectral response	UV: 0.185-0.260 μm ; IR: 4.3-4.8 μm
Detection ranges (at highest sensitivity setting for 1 ft ² [0.1 m ²] pan fire)	See Table 3 .
Sensitivity ranges	3 sensitivity ranges for 1 ft ² (0.1 m ²) n-Heptane pan fire
Field of view	Horizontal: 100°, vertical: 95°
Temperature range	Operating: -40 to +185 °F (-40 to +75 °C) Storage: -40 to +185 °F (-40 to +75 °C)
Humidity	Non-condensing relative humidity up to 100%

Table 2: Detection Response Time

Standard response time	Typically < 5 seconds
------------------------	-----------------------

Table 3: Detection Range

Fuel	ft/m
Gasoline (Petrol) ⁽¹⁾	93/28
N-Heptane ⁽¹⁾	93/28
Diesel fuel ⁽¹⁾	70/21
Methane ⁽²⁾	60/18
Liquefied petroleum gas (LPG) ⁽²⁾	60/18
Kerosene ⁽¹⁾	70/21
Jet fuel JP5 ⁽¹⁾	70/21
Jet fuel A1 ⁽¹⁾	70/21
Ethanol 95% ⁽¹⁾	57/17
Isopropyl alcohol (IPA) ⁽¹⁾	70/21
Methanol ⁽¹⁾	57/17
Ethylene glycol ⁽¹⁾	23/7
Solvents ⁽¹⁾	70/21
Flammable adhesive (flash point 140 °F < 60 °C) ⁽¹⁾	70/21
Butyl acrylate ⁽¹⁾	70/21
Vinyl acetate ⁽¹⁾	70/21
Oil paint ⁽¹⁾	70/21
Gun powder ⁽³⁾	93/28
Fireworks ⁽⁴⁾	10/3
Magnesium alloy ⁽⁵⁾	33/10
Polypropylene pellets ⁽¹⁾	60/18

Table 3: Detection Range (continued)

Office paper ⁽¹⁾	33/10
Wood ⁽¹⁾	33/10
Mineral oil (20w50) ⁽¹⁾	70/21
Cooking oil ⁽¹⁾	70/21
Lithium ion battery ⁽⁶⁾	75/23

- (1) 1 ft x 1 ft (0.3 m x 0.3 m) pan
- (2) 2.46 ft. (0.75 m) high, 0.82 ft. (0.25 m) width plume fire
- (3) 1.5-in. sq.
- (4) 10 pcs per test
- (5) Only for UV detector
- (6) One cell of battery per test

Table 4: Electrical Specifications

Operating voltage	24 Vdc nominal (18-32 Vdc)
Power consumption	Standby: Max. 3 W (8 W with heated window) Alarm: Max. 4.2 W (9.6 W with heated window)
Cable entries	2 x ¾-in.-14 NPT conduits or 2 x M25 x 1.5 mm ISO
Electrical input protection	According to EN50130
Electromagnetic compatibility	EMI/RFI protected to EN61000-6-3 and EN50130
Electrical interface	The detector includes 17 terminals with one wiring option

Table 5: Outputs

Relays	Alarm, fault, and auxiliary
Analog voltage output	Analog port malfunction: 0 V (< 0.5 V) Nomal: 2 V ± 0.3 V Alarm/Explosion: 5 V ± 0.3 V
0-20 mA (stepped)	±0.3 mA for 2 mA and 4 mA, and ±0.5 mA for 16 mA and 20 mA
HART [®] protocol	HART communications on the 0-20 mA analog current (FSK) - used for maintenance, configuration changes and asset management, available in mA source output wiring options
RS-485	RS-485 Modbus [®] compatible communication link that can be used in computer controlled installations

Table 6: Mechanical Specifications

Enclosure options	Electropolished Stainless Steel 316 Heavy duty copper free aluminum (less than 1%), polyurethane paint
Mounting	Tilt mount material-stainless steel 316 with electro polish finish
Dimensions	Detector 4 x 4.6 x 6.18-in. (100.6 x 117 x 155 mm)
Weight	Detector stainless steel: 6.3 lb. (2.9 kg) Detector: 2.8 lb. (1.3 kg) Tilt mount: 2.5 lb. (1.1 kg)
Environmental standards	DNV 2-4

Table 6: Mechanical Specifications (continued)

Water and dust	IP66 and IP68 per EN60529, NEMA 250 6P
----------------	--

Table 7: Approvals

Hazardous area	ATEX and IECEx	Ex II 2 G D Ex db eb IIC T4 Gb Ex tb IIIC T110 °C Db (-40 °C ≤ T _a ≤ +75 °C)
	FM/FMC/CSA	Class I Division 1, Groups B, C, and D, T4 Class II/III Division 1, Groups E, F, and G, T4 Class I Division 2, Groups B, C, and D, T4 T _a = -40 °C to +75 °C NEMA Type Rating 6P
	TR CU (EAC)	Ex db eb IIC T4 Gb X Ex tb IIIC T110 °C Db X (-40 °C ≤ T _a ≤ +75 °C)
Marine	MED "Wheelmark" (DNV)	
Performance	EN54-10 (VdS) FM3260	
Reliability	IEC61508 - SIL3 compatible	

Table 8: Accessories

Accessory	Part number
Flame simulator (Ex proof)	FS-1200
Tilt mount	877090
Duct mount (Ex proof)	877670
U-bolt/pole mount	2-in. (50.8 mm) pole: 789260-2
	3-in. (76.2 mm) pole: 789260-1
USB RS-485 harness kit	794079
Air shield	877650
Protective cover	877263 (conductive ABS plastic) ⁽¹⁾
	877163 (PU painted stainless steel 316)

(1) Supplied free of charge with the detector

For more information: www.emerson.com

©2021 Emerson. All rights reserved.

Spectrex is a mark of one of the Emerson family of companies.
All other marks are the property of their respective owners.

