



DCD-1E-IS/SIL

Intrinsically Safe Conventional Rate of Rise Heat Detector

Features

- ▶ SIL Level 2 approved
- ▶ Ideal for use in oil and gas environments
- ▶ Twin fire LEDs allow 360° viewing
- ▶ Electronics free mounting base
- ▶ Remote indicator output
- ▶ ATEX Classification to: II 1G EEx ia IIC T5 Tamb=55°C
- ▶ Suitable for installation in areas at Category 1 (inc all lower categories)
- ▶ Approved by LPCB and GL

Description

The DCD-1E-IS/SIL is an Intrinsically Safe Conventional Rate of Rise Heat Detector with a 60° fixed temperature element designed for use in hazardous areas. Which has been independently assessed and approved for use in a SIL2, low demand safety function with regards to random failure rates.

The unit also features a remote indicator output.



Specification

Operating Voltage	15 – 30 VDC
Quiescent Current (typ)	50 µA
Maximum Current In Alarm	50 mA
Operating Temperature Range	-10 °C to + 50 °C
Storage Temperature Range	-30 °C to + 70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP63
Colour / Case Material	White / ABS
Compatible Base / Base Height (mm)	YBN-R/4(IS) / 8
Weight (g) / Diameter (mm) / Height (mm)	97 / 100 / 40
Compatible Base / Height (mm)	YBN-R/4(IS) / 8
Fixing Centres (mm)	48 ~ 74
Approvals	LPCB, Germanischer Lloyd & ATEX – BAS01ATEX1281X

Ordering Codes

Product

Intrinsically Safe Conventional Photoelectric Smoke Detector

Part Number

SLR-E-IS/SIL



For further information visit www.hochikieurope.com/silapproved

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.