

## PowerMaster-10 G2

### PowerG-based Ultra-compact Wireless Alarm System



#### Features that Make a Difference:

- Unmatched affordability and performance
- Accommodates over 60 wireless devices:
  - Up to 30 zones
  - Up to 8 keypads, 8 keyfobs, 2 sirens, 4 repeaters
- Optional GSM/GPRS modules
- Extensive range of PowerG peripherals for every application
- Remote configuration and diagnostics with system status indications
- All devices are configured from the panel
- SirenNet - Leverages smoke detector buzzers for all alarms


#### A New Era in Intrusion Alarm Systems

PowerMaster-10 G2 is an ultra-compact, wireless alarm system suitable for advanced applications and heavy duty operations. It has a superior range, prolonged battery life and unmatched wireless robustness. Moreover, it provides outstanding full two-way wireless functionality with all peripherals.

Using Visonic's revolutionary PowerG network technology, PowerMaster-10 G2 fully answers the most demanding requirements facing the security industry today, as well as the challenges of tomorrow.

#### PowerG Robustness and Reliability

- Frequency Hopping Spread Spectrum (FHSS).
- Full two-way synchronized TDMA wireless network – Provides streamlined communication and improved channel efficiency.
- Huge transmission range of 2000m (6500ft) line of sight\* – Covers significantly larger premises than traditional systems, without repeaters.
- Highly secured AES-128 encrypted wireless communication – Surpasses the most demanding industry standards.
- Adaptive transmission power – Saves energy and significantly extends battery life.



\*Measured line-of-sight transmission range: 2000m (6500ft) at 8m (24ft), 750m (2500ft) at 2m (6.5ft)

## **New Toolset for Faster and Easier Installation**

- Special enrolment button on each device simplifies enrolment procedures.
- All devices are configured from the panel – No hardware switches and no need to re-open the peripherals once closed.
- Customized configuration templates enable configuration of the devices collectively.
- Visible signal quality indication shown on the device – Enables the installer to choose the optimal location without having to walk to the panel during installation.
- Powerful diagnostic tool indicates RF link quality, based on the previous 24 hours' statistics and on-demand bi-directional measurements, displaying immediate problems and enabling verification of the installation during house setup.

## **Powerful Tools for Central Monitoring Stations**

- Remote enrolment, configuration and review of all peripherals in the system.
- Initiate remote walk test with assistance from anyone in the house.
- Remote diagnostics of wireless connection and RF link quality for all peripherals – Based on the previous 24 hours' statistics and on-demand bi-directional measurements.

## **Green, Energy-saving System**

- Two-way, synchronized, spread spectrum communication eliminates unnecessary re-transmissions.
- Typical 5-8 years' battery life for all peripherals.
- Minimum power consumption and pollution due to adaptive transmission power that is determined according to the distance from the panel and level of RF interference.

## **Specifications**

RF network . . . . .	PowerG - Frequency hopping multi-channel (CDMA)
Frequency bands (Mhz) 433 – 434 868 - 869 912 - 919	
Hopping frequencies . . . . .	8 4 50
Encryption . . . . .	AES-128
Number of zones. . . . .	30
User codes . . . . .	8
Back-up battery ..12 hour back-up – 4.8V, 1300mAh, NiMH 24 hour back-up – 4.8V, 2200mAh, NiMH	
Dimensions . . . . .	196 x 180 x 55mm (7.62 x 7 x 2in)
Weight. . . . .	658g (23oz)
Power supply . . . . .	Internal or external according to local regulations
Reporting formats . . .	Analog: SIA, Contact ID, Scancom; IP: SIA IP, Visonic PowerNet
Communication . . . . .	PSTN, GSM, GPRS